

BRc ® Przekładnia zębata dwustopniowa

typ: 084 085 086 087 088 089 BRc

Numer rysunku	Wymiary gabarytowe [mm]								
	C3	W	W1	H	H2	F	F1	F2	F3
084 BRc	120	830	995	495	250	450	120	310	-
085 BRc	140	975	1170	593	300	550	120	380	-
086 BRc	180	1180	1346	690	350	630	130	460	-
087 BRc	195	1445	1730	890	450	770	160	260	300
088 BRc	225	1630	1936	990	500	870	180	280	360
089 BRc	270	1970	2320	1150	580	1295	220	370	590

Numer rysunku	Wielkość C	Prędkość obrotowa n [obr/min]	Wykonanie					
			A	B	C	D	E	
			Przełożenie					
			7,06	8,82	10,68	12,46	14,74	1
			Moc przenoszona przy prędkości obr."n" wałka szybkoobrotowego, [kW]					
084BRc 2W 450	425	750	59	52	43	37	31	
		1000	79	70	57	49	42	
		1500	92	84	72	63	53	
085BRc 2W 500	500	750	81	77	71	61	52	
		1000	107	103	92	78	67	

1500	125	115	101	89	77	63		
086BRc 2W 600	600	750	162	130	107	92	78	
		1000	206	174	144	123	104	
		1500	-	-	175	166	144	
087BRc 2W 750	750	750	200	200	166	142	120	
		1000	-	265	221	188	160	
		1500	-	-	-	-	210	
088BRc 2W 850	850	750	324	324	272	234	197	
		1000	-	-	361	313	263	
		1500	-	-	-	-	-	

Numer rysunku	Wielkość C	Prędkość obrotowa n [obr/min]	Wykonanie				
			H	J	K	L	M
			Przełożenie				
			21,84	25,56	31,50	36,85	44,01
			Moc przenoszona przy prędkości obr."n" wałk szybkoobrotowego, [kW]				
084BRc	425	750	21	16	13	11	9
		1000	28	21	17	15	13
		1500	34	28	22	21	18
085BRc	500	750	35	29	23	19	16
		1000	42	34	26	25	20
		1500	52	40	34	33	31
086BRc	600	750	52	45	37	31	25
		1000	70	60	48	41	33

1500	87	72	59	54	50	37	
087BRc	750	750	81	69	58	47	40
		1000	107	92	77	63	54
		1500	141	125	103	94	80
088BRc	850	750	132	114	96	77	66
		1000	177	151	124	103	88
		1500	192	174	147	140	132
089BRc 2W 1050	1050	750	368	316	258	221	184
		1000	493	420	346	287	243
		1500	-	-	-	-	-