



Koło jezdne napędzane typ BKh[™] DK16-078

typ: BKh[™]
NR / DK16-078

Główne parametry

Symbol	Wymiary										
	D (h11)	B	B1	B2	D1	D2 (D10)	DP	moduł m	liczba zębów z		
	[mm]										
1	400	60	110	65	440	80	320	8	40		
		65					400		50		
		60							320	40	
		65								400	50
		80	140								320
		90					400				50
		80							400		50
		90								400	50
2	500	65	120	70	540	90		420			10
		75					490	49			
		65						420	42		
		75							490	49	
		90	150							420	
		100					490			49	
		90						490		49	
		100							490	49	
3	630	70	130	80	680	100				540	10
		80					620			62	
		70						620		62	

80	329,0								
95	160	540	54	370	370,0				
110			396,0						
95		620	62	404,0					
110				410,0					
4	710	80	140	90	760	110	600	12	50
		90							
		80							
		90							
		120	200				600		50
		140							
		120							
		140							58
5	800	80	140	100	850	125	696	12	58
		90							
		80							
		90							
		95	200				696		58
		120							
		140							
		95							
120	792	66							
140									
6	900	90	150	110	950	140	784	14	56
		100							
		90							
		100							
		120	200				784		56

140	863,0		
120			905,0
	896	64	
140			893,0

Przykład oznaczenia

koła napędzanego według Karty Katalogowej DK16-078 o symbolu 4 i szerokości wytoczenia koła B=80mm

ZESTAW KOŁOWY NAPĘDZANY DK16-078-4-80

Zgodność z normami

koło według normy PN-M-84603:1989

Uwaga

Koło o innych parametrach może być wykonane po uprzednim uzgodnieniu.

